

Revision Date: 09/08/2010

Print Date: 2/18/2011 MSDS Number: R0366793

Version: 1.28

CARQUEST® ALL SEASON SAE 5W-20 MOTOR OIL CQ610

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Ashland Regulatory Information Number 1-800-325-3751 P.O. Box 2219 Telephone 614-790-3333

Columbus, OH 43216 Emergency telephone number 1-800-ASHLAND (1-800-274-

5263)

Product name CARQUEST® ALL SEASON SAE 5W-20 MOTOR OIL

Product code CQ610
Product Use Description No data

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid

CAUTION! PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE

IRRITATION.

Potential Health Effects

Exposure routes

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye contact

May cause mild eye irritation. Symptoms include stinging, tearing, and redness.

Skin contact

May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying and cracking of skin, and skin burns.

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

Inhalation



Revision Date: 09/08/2010

Print Date: 2/18/2011 MSDS Number: R0366793

Version: 1.28

CARQUEST® ALL SEASON SAE 5W-20 MOTOR OIL CQ610

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material:, Skin, lung (for example, asthma-like conditions)

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:, acne, stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways)

Target Organs

No data

Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). Used motor oil has been shown to cause skin cancer in laboratory animals continually exposed by repeated applications. Avoid prolonged or repeated skin contact.

Reproductive hazard

There are no data available for assessing risk to the fetus from maternal exposure to this material.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components	CAS-No.	Concentration	
HEAVY PARAFFINIC DISTILLATE	64742-54-7	>=50-<60%	
HEAVY PARAFFINIC DISTILLATE	64742-54-7	>=30-<40%	

4. FIRST AID MEASURES

Eyes



Revision Date: 09/08/2010

Print Date: 2/18/2011 MSDS Number: R0366793

Version: 1.28

CARQUEST® ALL SEASON SAE 5W-20 MOTOR OIL CQ610

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to physician

Hazards: Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Dry chemical, Carbon dioxide (CO2), Water spray

Hazardous combustion products

carbon dioxide and carbon monoxide, Hydrocarbons

Precautions for fire-fighting



Revision Date: 09/08/2010

Print Date: 2/18/2011 MSDS Number: R0366793

Version: 1.28

CARQUEST® ALL SEASON SAE 5W-20 MOTOR OIL CQ610

Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). DO NOT direct a solid stream of water or foam into hot, burning pools of liquid since this may cause frothing and increase fire intensity. Frothing can be violent and possibly endanger any firefighter standing too close to the burning liquid. Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning material with water used for cooling purposes.

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions

Prevent spreading over a wide area (e.g. by containment or oil barriers). Do not let product enter drains. Do not flush into surface water or sanitary sewer system.

Methods for cleaning up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

Other information

Comply with all applicable federal, state, and local regulations.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

Storage

Store in a cool, dry, ventilated area.



Revision Date: 09/08/2010

Print Date: 2/18/2011 MSDS Number: R0366793

Version: 1.28

CARQUEST® ALL SEASON SAE 5W-20 MOTOR OIL CQ610

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

HYDROTREATED PARAFFINIC DISTILLATE, DEWAXED

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Eye protection

Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection

Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

Wear resistant gloves (consult your safety equipment supplier).

Respiratory protection

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

9. PHYSICAL AND CHEMICAL PROPERTIES



Revision Date: 09/08/2010

Print Date: 2/18/2011 MSDS Number: R0366793

Version: 1.28

CARQUEST® ALL SEASON SAE 5W-20 **MOTOR OIL**

CQ610

Physical state liquid

Form no data available Colour no data available Odour no data available Boiling point/boiling range no data available Melting point/range no data available **Sublimation point** no data available pН no data available

Flash point > 390 °F / > 199 °C Cleveland open cup

Ignition temperature no data available **Evaporation rate** no data available Lower explosion limit/Upper explosion limit 1 %(V) / 6 %(V) Particle size no data available

0.001 hPa @ 68 °F / 20 °C Calculated Vapor Vapour pressure

Pressure

no data available Relative vapour density

Density 0.8555 g/cm3 @ 60.01 °F / 15.56 °C

7.15 lb/gal @ 60.00 °F / 15.56 °C

Bulk density No data

Water solubility no data available **Solubility** no data available Partition coefficient: n-octanol/water no data available log Pow no data available **Autoignition temperature** no data available

Viscosity, dynamic no data available

Viscosity, kinematic 8.5 mm2/s

Solids in Solution no data available **Decomposition temperature** no data available **Burning** number no data available **Dust explosion constant** no data available Minimum ignition energy no data available

10. STABILITY AND REACTIVITY

Stability

Stable

Conditions to avoid



Revision Date: 09/08/2010

Print Date: 2/18/2011 MSDS Number: R0366793

Version: 1.28

CARQUEST® ALL SEASON SAE 5W-20 MOTOR OIL CQ610

None known.

Incompatible products

Strong oxidizing agents

Hazardous decomposition products

carbon dioxide and carbon monoxide, Hydrocarbons

Hazardous reactions

Product will not undergo hazardous polymerization.

Thermal decomposition

No data

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity

HEAVY PARAFFINIC DISTILLATE : LD 50 Rat: > 15 g/kg

HEAVY PARAFFINIC DISTILLATE : LD 50 Rat: > 15 g/kg

Acute inhalation toxicity

HEAVY PARAFFINIC DISTILLATE : no data available

HEAVY PARAFFINIC DISTILLATE : no data available

Acute dermal toxicity

HEAVY PARAFFINIC DISTILLATE : LD 50

Rabbit: > 5 g/kg

HEAVY PARAFFINIC DISTILLATE : LD 50

Rabbit: > 5 g/kg

12. ECOLOGICAL INFORMATION



Revision Date: 09/08/2010

Print Date: 2/18/2011 MSDS Number: R0366793

Version: 1.28

CARQUEST® ALL SEASON SAE 5W-20 MOTOR OIL CQ610

Biodegradability

HEAVY PARAFFINIC DISTILLATE : no data available

HEAVY PARAFFINIC DISTILLATE : no data available

Bioaccumulation

HEAVY PARAFFINIC DISTILLATE : no data available

HEAVY PARAFFINIC DISTILLATE : no data available

Ecotoxicity effects

Toxicity to fish

HEAVY PARAFFINIC DISTILLATE : no data available

HEAVY PARAFFINIC DISTILLATE : no data available

Toxicity to daphnia and other aquatic invertebrates.

HEAVY PARAFFINIC DISTILLATE : no data available

HEAVY PARAFFINIC DISTILLATE : no data available

Toxicity to algae

HEAVY PARAFFINIC DISTILLATE : no data available

HEAVY PARAFFINIC DISTILLATE : no data available

Toxicity to bacteria

HEAVY PARAFFINIC DISTILLATE : no data available

HEAVY PARAFFINIC DISTILLATE : no data available

Biochemical Oxygen Demand (BOD)

HEAVY PARAFFINIC DISTILLATE : no data available

HEAVY PARAFFINIC DISTILLATE : no data available

Chemical Oxygen Demand (COD)

HEAVY PARAFFINIC DISTILLATE : no data available



Revision Date: 09/08/2010

Print Date: 2/18/2011 MSDS Number: R0366793

Version: 1.28

CARQUEST® ALL SEASON SAE 5W-20 MOTOR OIL CQ610

HEAVY PARAFFINIC DISTILLATE : no data available

Additional ecological information

HEAVY PARAFFINIC DISTILLATE : no data available

HEAVY PARAFFINIC DISTILLATE : no data available

13. DISPOSAL CONSIDERATIONS

Waste disposal methods

Destroy by liquid incineration. Contaminated absorbent may be deposited in a landfill in accordance with local, state and federal regulations. For assistance with your waste management needs including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION

REGULATION

ID	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
NUMBER		CLASS	HAZARDS	GROUP	POLLUTANT
					/ LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

U.S. DOT - RAIL

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TRANSPORT CANADA - ROAD

Not dangerous goods

TRANSPORT CANADA - RAIL

Not dangerous goods



Revision Date: 09/08/2010

Print Date: 2/18/2011 MSDS Number: R0366793

Version: 1.28

CARQUEST® ALL SEASON SAE 5W-20 MOTOR OIL CQ610

TRANSPORT CANADA - INLAND WATERWAYS

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

15. REGULATORY INFORMATION

California Prop. 65

Proposition 65 warnings are not required for this product based	
on the results of a risk assessment.	

SARA Hazard Classification

No SARA Hazards

New Jersey RTK Label Information

HEAVY PARAFFINIC DISTILLATE 64742-54-7 HEAVY PARAFFINIC DISTILLATE 64742-54-7

LUBRICANT ADDITIVE

HYDROTREATED PARAFFINIC DISTILLATE, DEWAXED

Pennsylvania RTK Label Information

HEAVY PARAFFINIC DISTILLATE 64742-54-7 HEAVY PARAFFINIC DISTILLATE 64742-54-7



Revision Date: 09/08/2010

Print Date: 2/18/2011 MSDS Number: R0366793

Version: 1.28

CARQUEST® ALL SEASON SAE 5W-20 MOTOR OIL CQ610

LUBRICANT ADDITIVE HYDROTREATED PARAFFINIC DISTILLATE, DEWAXED

Notification status

US. Toxic Substances Control Act y (positive listing) Canada. Canadian Environmental Protection Act (CEPA). y (positive listing) Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133) Australia. Industrial Chemical (Notification and Assessment) y (positive listing) Act New Zealand. Inventory of Chemicals (NZIoC), as published y (positive listing) by ERMA New Zealand Japan. Kashin-Hou Law List e (special case) Korea. Toxic Chemical Control Law (TCCL) List y (positive listing) Philippines. The Toxic Substances and Hazardous and Nuclear y (positive listing) Waste Control Act China. Inventory of Existing Chemical Substances q (quantity restricted)

	HMIS	NFPA
Health	1	1
Flammability	1	1
Physical hazards		
Instability		0
Specific Hazard		

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).