SAFETY DATA SHEET

DB584-03

| Section 1. Identification |
|---------------------------|
|---------------------------|

| Product name | : DIRT FIGHTER® Eggshell Interior Acrylic Latex Enamel Paint + Primer White |
|--|--|
| Product code | : DB584-03 |
| Other means of identification | : Not available. |
| Product type | : Liquid. |
| Relevant identified uses of t | he substance or mixture and uses advised against |
| Not applicable. | |
| Manufacturer | : DUTCH BOY 101 Prospect Avenue N.W. Cleveland, OH 44115 |
| Emergency telephone number of the company | : (216) 566-2917 |
| Product Information Telephone Number | : Not available. |
| Regulatory Information Telephone Number | : (216) 566-2902 |
| Transportation Emergency Telephone Number | : (800) 424-9300 |

Section 2. Hazards identification

| OSHA/HCS status | : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). |
|--|---|
| Classification of the substance or mixture | : SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A CARCINOGENICITY - Category 1A |
| | Percentage of the mixture consisting of ingredient(s) of unknown oral toxicity: 34.2% Percentage of the mixture consisting of ingredient(s) of unknown dermal toxicity: 34.2% Percentage of the mixture consisting of ingredient(s) of unknown inhalation toxicity: 34. 2% |
| GHS label elements | |
| Hazard pictograms | |
| Signal word | : Danger |
| Hazard statements | : Causes serious eye irritation. Causes skin irritation. May cause cancer. |
| Precautionary statements | |
| General | : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. |
| Prevention | : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Wash hands thoroughly after handling. |

| Date of issue/Date | e of revision | : 3/2/2018 | Date of previous issue | : 2/16/2018 | Version | : 7.02 | 1/11 |
|--------------------|-------------------------------|------------------------|----------------------------|-------------|---------|---------------|------|
| DB584-03 | DIRT FIGHTER® Eggshe White | ell Interior Acrylic L | atex Enamel Paint + Primer | | SHW-85- | NA-GHS-US | |

Section 2. Hazards identification

| Response | : IF exposed or concerned: Get medical attention. IF ON SKIN: Wash with plenty of |
|----------------------------------|--|
| | soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. |
| Storage | : Store locked up. |
| Disposal | : Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| Supplemental label elements | WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Adequate ventilation required when sanding or abrading the dried film. If Adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release Crystalline Silica which has been shown to cause lung damage and cancer under long term exposure. This product contains a Significant New Use Rule (SNUR) Chemical. Do not allow this product to enter drains, sewers, wastewater treatment systems, groundwater, streams, lakes or ponds. See Environmental Data Sheet (EDS) for additional details. |
| | Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage. |
| Hazards not otherwise classified | : None known. |

Section 3. Composition/information on ingredients

| Substance/mixture | : Mixture |
|-------------------|------------------|
| Other means of | : Not available. |
| identification | |

CAS number/other identifiers

| Ingredient name | % by weight | CAS number |
|---------------------------------------|-------------|------------|
| Titanium Dioxide | ≥10 - ≤25 | 13463-67-7 |
| Calcium Carbonate | ≥10 - <20 | 1317-65-3 |
| Crystalline Silica, respirable powder | ≤0.3 | 14808-60-7 |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

| Eye contact | Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention. |
|--------------|---|
| Inhalation | : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |
| Skin contact | : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse. |

| Date of issue/Date | of revision | : 3/2/2018 | Date of previous issue | : 2/16/2018 | Version | :7.02 | 2/11 |
|--------------------|--------------------------------|-----------------------|----------------------------|-------------|---------|-----------|------|
| DB584-03 | DIRT FIGHTER® Eggshel White | Il Interior Acrylic L | atex Enamel Paint + Primer | | SHW-85- | NA-GHS-US | |

Section 4. First aid measures

| Ingestion | : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |
|--------------------------------|---|
| Most important symptoms/e | effects, acute and delayed |
| Potential acute health effe | <u>cts</u> |
| Eye contact | : Causes serious eye irritation. |
| Inhalation | : No known significant effects or critical hazards. |
| Skin contact | : Causes skin irritation. |
| Ingestion | : No known significant effects or critical hazards. |
| <u>Over-exposure signs/sym</u> | <u>otoms</u> |
| Eye contact | : Adverse symptoms may include the following: pain or irritation watering redness |
| Inhalation | : No specific data. |
| Skin contact | : Adverse symptoms may include the following: irritation redness |
| Ingestion | : No specific data. |
| Indication of immediate me | dical attention and special treatment needed, if necessary |
| Notes to physician | Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. |
| Specific treatments | : No specific treatment. |
| Protection of first-aiders | : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. |

See toxicological information (Section 11)

Section 5. Fire-fighting measures

| Extinguishing media | |
|--|--|
| Suitable extinguishing media | : Use an extinguishing agent suitable for the surrounding fire. |
| Unsuitable extinguishing media | : None known. |
| Specific hazards arising from the chemical | : In a fire or if heated, a pressure increase will occur and the container may burst. |
| Hazardous thermal decomposition products | : Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides |

Section 5. Fire-fighting measures

| Special protective actions for fire-fighters | Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. |
|--|---|
| Special protective equipment for fire-fighters | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. |

Section 6. Accidental release measures

| Personal precautions, protec | tiv | e equipment and emergency procedures |
|--------------------------------|-----|---|
| For non-emergency personnel | : | No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. |
| For emergency responders | : | If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". |
| Environmental precautions | : | This product contains a Significant New Use Rule (SNUR) Chemical. Do not allow this product to enter drains, sewers, wastewater treatment systems, groundwater, streams, lakes or ponds. See Environmental Data Sheet (EDS) for additional details. |
| | | Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). |
| Methods and materials for co | nta | ainment and cleaning up |
| Small spill | : | Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. |
| Large spill | : | Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal. |

Section 7. Handling and storage

Precautions for safe handling

| Protective measures | : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. |
|--|--|
| Advice on general occupational hygiene | : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. |

Section 7. Handling and storage

| Conditions for safe storage, including any incompatibilities | : | Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use. |
|--|---|---|
|--|---|---|

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

| Ingredient name | Exposure limits |
|---------------------------------------|---|
| Titanium Dioxide | ACGIH TLV (United States, 3/2016). TWA: 10 mg/m ³ 8 hours. OSHA PEL (United States, 6/2016). |
| Calcium Carbonate | TWA: 15 mg/m ³ 8 hours. Form: Total dust NIOSH REL (United States, 10/2016). TWA: 5 mg/m ³ 10 hours. Form: Respirable |
| | fraction TWA: 10 mg/m ³ 10 hours. Form: Total OSHA PEL (United States, 6/2016). TWA: 5 mg/m ³ 8 hours. Form: Respirable fraction TWA: 15 mg/m ³ 8 hours. Form: Total dust |
| Crystalline Silica, respirable powder | OSHA PEL Z3 (United States, 6/2016). TWA: 250 mppcf / (%SiO2+5) 8 hours. Form: Respirable TWA: 10 mg/m³ / (%SiO2+2) 8 hours. Form: Respirable OSHA PEL (United States, 6/2016). TWA: 50 μg/m³ 8 hours. Form: Respirable dust ACGIH TLV (United States, 3/2016). TWA: 0.025 mg/m³ 8 hours. Form: Respirable fraction NIOSH REL (United States, 10/2016). TWA: 0.05 mg/m³ 10 hours. Form: respirable dust |

Occupational exposure limits (Canada)

| Ingredient name | Exposure limits | | | | |
|-----------------|-----------------|--|--|--|--|
| None. | | | | | |
| | | | | | |

Occupational exposure limits (Mexico) Ingredient name Exposure limits

None.

Appropriate engineering controls : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits

Environmental exposure controls

- local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
 This product contains a Significant New Use Rule (SNUR) Chemical. Do not allow this product to enter during excerne user to extend to enter a significant for the statement of the s
- this product to enter drains, sewers, wastewater treatment systems, groundwater, streams, lakes or ponds. See Environmental Data Sheet (EDS) for additional details.

Section 8. Exposure controls/personal protection

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

| Individual protection measures | |
|--------------------------------|--|
| | Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. |
| Eye/face protection : | Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. |
| Skin protection | |
| Hand protection : | Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. |
| Body protection : | Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Other skin protection : | Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Respiratory protection : | Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. |

Section 9. Physical and chemical properties

| <u>Appearance</u> | |
|--|----------------------------------|
| Physical state | : Liquid. |
| Color | : White. |
| Odor | : Not available. |
| Odor threshold | : Not available. |
| рН | : 9 |
| Melting point | : Not available. |
| Boiling point | : 100°C (212°F) |
| Flash point | : Closed cup: >93.3°C (>199.9°F) |
| Evaporation rate | : 0.09 (butyl acetate = 1) |
| Flammability (solid, gas) | : Not available. |
| Lower and upper explosive (flammable) limits | : Not available. |
| Vapor pressure | : 2.3 kPa (17.5 mm Hg) [at 20°C] |
| Vapor density | : 1 [Air = 1] |
| Relative density | : 1.35 |
| Solubility | : Not available. |
| Partition coefficient: n- octanol/water | : Not available. |
| Auto-ignition temperature | : Not available. |

| Date of issue/Date | of revision | : 3/2/2018 | Date of previous issue | : 2/16/2018 | Version | : 7.02 | 6/11 |
|--------------------|---------------------------------|---------------------|---------------------------|-------------|----------|-----------|------|
| DB584-03 | DIRT FIGHTER® Eggshell White | Interior Acrylic La | tex Enamel Paint + Primer | | SHW-85-I | NA-GHS-US | |

Section 9. Physical and chemical properties

| Decomposition temperature | 1 | Not available. |
|---------------------------|---|--|
| Viscosity | : | Kinematic (40°C (104°F)): >0.205 cm²/s (>20.5 cSt) |
| Molecular weight | : | Not applicable. |
| Aerosol product | | |
| Heat of combustion | : | 1.087 kJ/g |

Section 10. Stability and reactivity

| Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |
|------------------------------------|--|
| Incompatible materials | : No specific data. |
| Conditions to avoid | : No specific data. |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| Chemical stability | : The product is stable. |
| Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Not available.

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-------------------------|----------------------|---------|-------|--|-------------|
| Titanium Dioxide | Skin - Mild irritant | Human | | 72 hours 300 Micrograms Intermittent | - |

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

| Product/ingredient name | OSHA | IARC | NTP |
|--|------|---------|--------------------------------------|
| Titanium Dioxide Crystalline Silica, respirable powder | - | 2B 1 | - Known to be a human carcinogen. |

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

| Date of issue/Date | of revision | : 3/2/2018 | Date of previous issue | : 2/16/2018 | Version | : 7.02 | 7/11 |
|--------------------|-----------------------------|-----------------------|----------------------------|-------------|---------|-----------|------|
| DB584-03 | DIRT FIGHTER® Eggshel White | I Interior Acrylic La | atex Enamel Paint + Primer | | SHW-85- | NA-GHS-US | |

Section 11. Toxicological information

| Name | | Route of exposure | Target organs |
|-------------------|------------|-------------------|------------------------------|
| Calcium Carbonate | Category 3 | | Respiratory tract irritation |

Specific target organ toxicity (repeated exposure)

| Name | | Route of exposure | Target organs |
|---------------------------------------|------------|----------------------|----------------|
| Crystalline Silica, respirable powder | Category 1 | Inhalation | Not determined |

Aspiration hazard

Not available.

| Information on the likely routes of exposure | : Not available. |
|---|--|
| Potential acute health effe | <u>icts</u> |
| Eye contact | : Causes serious eye irritation. |
| Inhalation | : No known significant effects or critical hazards. |
| Skin contact | : Causes skin irritation. |
| Ingestion | : No known significant effects or critical hazards. |
| Symptoms related to the j | physical, chemical and toxicological characteristics |
| Eye contact | : Adverse symptoms may include the following: pain or irritation watering redness |
| Inhalation | : No specific data. |
| Skin contact | : Adverse symptoms may include the following: irritation redness |
| Ingestion | : No specific data. |
| Short term exposure Potential immediate effects | fects and also chronic effects from short and long term exposure : Not available. |
| Potential delayed effects | : Not available. |
| Long term exposure Potential immediate effects | : Not available. |
| Potential delayed effects | : Not available. |
| Potential chronic health e | ffects |
| Not available. | |
| General | : No known significant effects or critical hazards. |
| Carcinogenicity | : May cause cancer. Risk of cancer depends on duration and level of |
| Mutagenicity | No known significant effects or critical hazards. |
| Teratogenicity | : No known significant effects or critical hazards. |
| Developmental effects | : No known significant effects or critical hazards. |
| Fertility effects | : No known significant effects or critical hazards. |
| | |

Numerical measures of toxicity

| Date of issue/Date | e of revision | : 3/2/2018 | Date of previous issue | : 2/16/2018 | Version : 7.02 | 8/11 |
|--------------------|-------------------------------|------------------------|-----------------------------|-------------|------------------|------|
| DB584-03 | DIRT FIGHTER® Eggsho White | ell Interior Acrylic I | _atex Enamel Paint + Primer | | SHW-85-NA-GHS-US | |

exposure.

Section 12. Ecological information

| Toxicity | | | |
|--|---|---|---|
| Product/ingredient name | Result | Species | Exposure |
| Titanium Dioxide | Acute LC50 >1000000 µg/l Marine water | Fish - Fundulus heteroclitus | 96 hours |
| Persistence and degradabili | itv | | |
| Not available. | | | |
| Bioaccumulative potential | | | |
| Not available. | | | |
| <u>Mobility in soil</u> | | | |
| Soil/water partition coefficient (Koc) | : Not available. | | |
| Other adverse effects | : No known significant effects or critical | nazards. | |
| Section 13. Dispo | sal considerations | | |
| Disposal methods | : This product contains a Significant this product to enter drains, sewers streams, lakes or ponds. See Enviro details. | wastewater treatment systems | s, groundwater |
| | The generation of waste should be avo of this product, solutions and any by-pr requirements of environmental protecti regional local authority requirements. I via a licensed waste disposal contracto the sewer unless fully compliant with th Waste packaging should be recycled. when recycling is not feasible. This may safe way. Care should be taken when cleaned or rinsed out. Empty containe Avoid dispersal of spilled material and and sewers. | oducts should at all times comply on and waste disposal legislation Dispose of surplus and non-recyc r. Waste should not be disposed e requirements of all authorities v Incineration or landfill should only aterial and its container must be d handling emptied containers that rs or liners may retain some product | with the and any able products of untreated to vith jurisdiction. be considered isposed of in a have not been uct residues. |

Section 14. Transport information

| | DOT Classification | TDG Classification | Mexico Classification | ΙΑΤΑ | IMDG |
|-------------------------------|-------------------------------|--------------------------------|--------------------------|----------------|----------------|
| UN number | Not regulated. | Not regulated. | Not regulated. | Not regulated. | Not regulated. |
| UN proper shipping name | - | - | - | - | - |
| Transport hazard class(es) | - | - | - | - | - |
| Packing group | - | - | - | - | - |
| Date of issue/Date of rev | vision : 3/2/201 | 8 Date of previous | issue : 2/16/201 | 8 Versi | on : 7.02 9/11 |
| DB584-03 DIRT White | FIGHTER® Eggshell Interior Ac | crylic Latex Enamel Paint + Pr | imer | SHW | -85-NA-GHS-US |

| Environmental hazards | No. | No. | No. | No. | No. |
|---|-----|--|--|--|--|
| Additional information | - | - | - | - | - |
| Special precautio | | : Multi-modal shipping des consider container sizes. mode of transport (sea, a suitably for that mode of prior to shipment, and co responsibility of the perso unloading dangerous goo substances and on all ac | The presence air, etc.), does transport. All p mpliance with on offering the ods must be tr | e of a shipping desc not indicate that the backaging must be r the applicable regu product for transpo ained on all of the ri | ription for a particular product is packaged eviewed for suitability lations is the sole rt. People loading and sks deriving from the |
| Transport in bulk to Annex II of MAF the IBC Code | | : Not available. | | | |
| | | Proper shipping name | : Not av | ailable. | |
| | | Ohim france | : Not av | ailabla | |
| | | Ship type | . NUL av | allable. | |

Section 15. Regulatory information

U.S. Federal regulations : TSCA 5(a)2 final significant new use rules: Nonylphenoxypoly(ethoxy)ethanol This product contains a Significant New Use Rule (SNUR) Chemical. Do not allow this product to enter drains, sewers, wastewater treatment systems, groundwater, streams, lakes or ponds. See Environmental Data Sheet (EDS) for additional details.

SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

| | | Justification | | | | | |
|-----------------|---|---------------|--------------------|-----------------------------|-------------|--|-------|
| SERIOUS | SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A CARCINOGENICITY - Category 1A | | | | | Calculation method Calculation method Calculation method | |
| History | | | | | | | |
| Date of pri | nting | : | 3/2/2018 | | | | |
| | | : | 3/2/2018 | | | | |
| Date of issue/D | Date of revision | | : 3/2/2018 | Date of previous issue | : 2/16/2018 | Version : 7.02 | 10/11 |
| DB584-03 | DIRT FIGHTER® White | B Eggshel | I Interior Acrylic | Latex Enamel Paint + Primer | | SHW-85-NA-GHS-US | 6 |

Section 16. Other information

| Date of issue/Date of revision | |
|--------------------------------|---|
| Date of previous issue | : 2/16/2018 |
| Version | : 7.02 |
| Key to abbreviations | : ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations |

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by Sherwin-Williams, including but not limited to the incorporation of non Sherwin-Williams products or the use or addition of products in proportions not specified by Sherwin-Williams. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer: the customer/buver/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.