

VOC COMPLIANT LACQUER THINNER

TECHNICAL DATA SHEET

477



SUNNYSIDE VOC COMPLIANT LACQUER THINNER

DESCRIPTION

VOC Compliant Lacquer Thinner is the recommended lacquer thinner and clean up solvent when a low VOC thinner is required. Fast evaporating and extremely flammable.

ITEM NUMBERS & SIZES

Pint	Quart	1-Gallon	2.5-Gal.	5-Gal.	55-Gal.
	47732	477G1		477G5	

HAZARDOUS INGREDIENTS

Ingredient	CAS#
Acetone	67-64-1
Parachlorobenzo-trifluoride	98-56-6
2-Butoxyethanol	111-76-2

PHYSICAL PROPERTIES

Typical Properties	Results
GRAVITY, (60 °F)	
API	
SPECIFIC DENSITY (Lb./GAL)	0.85
DISTILLATION RANGE IBP ° F	7.08
FREEZING POINT, °F (°C)	133
KAURI BUTANOL (Kb) VALUE	
ANILINE POINT, °F	
FLASH POINT, T.C.C. °F	0
FLAMMABLE LIMITS IN AIR, % BY VOLUME	
LOWER, AT 100°F (38°C)	
UPPER, AT 200°F (93°C)	
AUTOIGNITION TEMPERATURE, °F (°C)	
COLOR (P t-Co) Max.	5
DOCTOR TEST	
CORROSION, 3 HRS. @ 212 °F	
NON-VOLATILES, g/100ml	
ACIDITY (as Acetic Acid)	
ALKALINITY (AS NH ₃ , WT%)	
EVAPORATION RATE	Slower than ether
APPEARANCE	Clear, water-white
ODOR	Characteristic, Nonresidual
VAPOR PRESSURE, mm Hg @ 20 °C	
REFRACTIVE INDEX, @ 20 °C	
SULFUR CONTENT, PPM	
PURITY, by G.C., Wt%	
WATER CONTENT, Wt%	
WATER MISCIBILITY	Partial
DOT SHIPPING NAME	Paint related material
DOT CLASSIFICATION	Hazard Class III
SHIPPING Wt. at 20 °C	7.08
V.O.C. (g/L)	24 g/L

These properties are representative of typical inspections. They do not constitute product specifications. Consult MSDS sheet for additional information.

PRODUCT IMAGE



SAFETY INFORMATION

HEALTH:	2
FIRE:	3
REACTIVITY:	1

PRODUCT APPLICATION

VOC Compliant General Purpose Thinner effectively thins most oil based paints, stains and varnishes. Use for clean up after painting.

TEST METHOD

ASTM	Applied
D-278	
D-1298	■
D-86	■
D-1133	
D-611	
D-56	■
D-1255	
D-156	■
D-484	
D-130	
D-1353	
D-847	
D-1614	
D-1296	■
D-1218	
D-1266	
D-1364	
D-1722	

See MSDS sheet for additional Health, Safety, Handling and Regulatory Information available on our website at www.sunnysidecorp.com/msds.html