



# SAFETY DATA SHEET

Revision Date 17-Jun-2015

Version 1

## 1. IDENTIFICATION

### Product identifier

**Product Name** 135EA HEAVY DUTY RUBBERIZED UNDERCOATING 16OZ AE

### Other means of identification

**Product Code** 81833

**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** Undercoating - Aerosol

**Uses advised against** No information available

### Details of the supplier of the safety data sheet

#### Manufacturer Address

ITW Permatex  
10 Columbus Blvd.  
Hartford, CT 06106 USA

#### Distributor

ITW Permatex Canada  
35 Brownridge Road, Unit 1  
Halton Hills, ON Canada L7G 0C6  
Telephone: (800) 924-6994

**Company Phone Number** 1-87-Permatex  
(877) 376-2839

**24 Hour Emergency Phone Number** Chem-Tel: 800-255-3924  
International Emergency:  
00+1+ 813-248-0585  
Contract Number: MIS0003453

**E-mail address** mail@permatex.com

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable aerosols	Category 1

### Label elements

#### Emergency Overview

#### **Danger**

Causes skin irritation  
Suspected of damaging fertility or the unborn child  
Causes damage to organs through prolonged or repeated exposure  
May be fatal if swallowed and enters airways  
Extremely flammable aerosol

**Appearance** Black

**Physical state** Liquid Aerosol

**Odor** Solvent

**Precautionary Statements - Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Do not eat, drink or smoke when using this product  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
 Do not spray on an open flame or other ignition source  
 Pressurized container: Do not pierce or burn, even after use

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention  
 Specific treatment (see supplemental first aid instructions on this label)  
 IF ON SKIN: Wash with plenty of soap and water  
 If skin irritation occurs: Get medical advice/attention  
 Take off contaminated clothing and wash before reuse  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do NOT induce vomiting

**Precautionary Statements - Storage**

Store locked up  
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Not applicable

**Other Information**

- Harmful to aquatic life with long lasting effects
- The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0.1 % w/w 1,3-butadiene (EINECS No. 203-450-8). If the substance is not classified as a carcinogen or mutagen, at least the S-phrases (2-)9-16 (Table 3.2) should apply. This note applies only to certain complex oil-derived substances in Part 3
- The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7).

Unknown acute toxicity                      37.5 % of the mixture consists of ingredient(s) of unknown toxicity

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

**substance(s)**

Chemical Name	CAS No	Weight-%	Trade Secret
PETROLEUM GASES, LIQUEFIED, SWEETENED	68476-86-8	10 - 30	*
ASPHALT, OXIDIZED	64742-93-4	10 - 30	*
TOLUENE	108-88-3	7 - 13	*

STODDARD SOLVENT	8052-41-3	5 - 10	*
TALC	14807-96-6	3 - 7	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

##### Description of first aid measures

<b>General advice</b>	Get medical advice/attention if you feel unwell.
<b>Eye contact</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
<b>Skin contact</b>	IF ON SKIN: Wash skin with soap and water. If skin irritation persists, call a physician. Wash contaminated clothing before reuse.
<b>Inhalation</b>	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.
<b>Ingestion</b>	IF SWALLOWED: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician.
<b>Self-protection of the first aider</b>	Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

##### Most important symptoms and effects, both acute and delayed

**Symptoms** See section 2 for more information.

##### Indication of any immediate medical attention and special treatment needed

**Note to physicians** Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

Carbon dioxide (CO<sub>2</sub>), Dry chemical, Foam

##### Unsuitable extinguishing media

None.

##### Specific hazards arising from the chemical

Extremely flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

##### Explosion data

**Sensitivity to Mechanical Impact** None.

**Sensitivity to Static Discharge** None.

##### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

#### 6. ACCIDENTAL RELEASE MEASURES

##### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Ensure adequate ventilation, especially in confined areas. Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Take precautionary measures against static discharges. Remove all sources of ignition. Contents under pressure. Do not puncture or incinerate cans.

**Environmental precautions**

**Environmental precautions** See Section 12 for additional ecological information.

**Methods and material for containment and cleaning up**

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Advice on safe handling** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Contents under pressure. Do not puncture or incinerate cans. Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Store locked up. Do not expose to temperatures exceeding 50 °C/122 °F.

**Incompatible materials** Strong oxidizing agents

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
TOLUENE 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m <sup>3</sup> Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m <sup>3</sup> STEL: 150 ppm STEL: 560 mg/m <sup>3</sup>
STODDARD SOLVENT 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m <sup>3</sup>	IDLH: 20000 mg/m <sup>3</sup> Ceiling: 1800 mg/m <sup>3</sup> 15 min TWA: 350 mg/m <sup>3</sup>
TALC 14807-96-6	TWA: 2 mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	(vacated) TWA: 2 mg/m <sup>3</sup> respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more, use Quartz limit	IDLH: 1000 mg/m <sup>3</sup> TWA: 2 mg/m <sup>3</sup> containing no Asbestos and <1% Quartz respirable dust

NIOSH IDLH *Immediately Dangerous to Life or Health*

**Other Information** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

**Appropriate engineering controls**

**Engineering Controls** Showers  
Eyewash stations  
Ventilation systems

**Individual protection measures, such as personal protective equipment**

<b>Eye/face protection</b>	Wear safety glasses with side shields (or goggles).
<b>Skin and body protection</b>	Wear protective gloves and protective clothing.
<b>Respiratory protection</b>	Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.
<b>General Hygiene Considerations</b>	Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

<b>Physical state</b>	Liquid; Aerosol
<b>Appearance</b>	Black
<b>Odor</b>	Solvent
<b>Odor threshold</b>	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
<b>pH</b>	No information available	
<b>Melting point / freezing point</b>	No information available	
<b>Boiling point / boiling range</b>	> 38 °C / >100 °F	
<b>Flash point</b>	No information available	Gives a flame projection at full valve opening or flashback at any degree of valve opening
<b>Evaporation rate</b>	< 1	Butyl acetate = 1
<b>Flammability (solid, gas)</b>	No information available	
<b>Flammability Limit in Air</b>		
<b>Upper flammability limit:</b>	No information available	
<b>Lower flammability limit:</b>	No information available	
<b>Vapor pressure</b>	No information available	
<b>Vapor density</b>	>1	Air = 1
<b>Relative density</b>	1.02	
<b>Water solubility</b>	No information available	
<b>Solubility in other solvents</b>	No information available	
<b>Partition coefficient</b>	No information available	
<b>Autoignition temperature</b>	No information available	
<b>Decomposition temperature</b>	No information available	
<b>Kinematic viscosity</b>	No information available	
<b>Dynamic viscosity</b>	No information available	
<b>Explosive properties</b>	No information available	
<b>Oxidizing properties</b>	No information available	

**Other Information**

<b>Softening point</b>	No information available
<b>Molecular weight</b>	No information available
<b>VOC Content (%)</b>	39.5%
<b>Density</b>	No information available
<b>Bulk density</b>	No information available

**10. STABILITY AND REACTIVITY**

**Reactivity**  
No data available

**Chemical stability**  
Stable under recommended storage conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks. Take precautionary measures against static discharges.

**Incompatible materials**

Strong oxidizing agents

**Hazardous Decomposition Products**

Carbon oxides

Oxides of sulfur

Hydrogen sulfide

**11. TOXICOLOGICAL INFORMATION**

**Information on likely routes of exposure**

<b>Inhalation</b>	Harmful by inhalation.
<b>Eye contact</b>	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.
<b>Skin contact</b>	May cause skin irritation and/or dermatitis.
<b>Ingestion</b>	Harmful if swallowed. Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
ASPHALT, OXIDIZED 64742-93-4	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	-
TOLUENE 108-88-3	= 2600 mg/kg ( Rat )	= 12000 mg/kg ( Rabbit )	= 12.5 mg/L ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** No information available.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** No information available.  
**Germ cell mutagenicity** No information available.  
**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
ASPHALT, OXIDIZED 64742-93-4	-	Group 2A	-	X
TOLUENE 108-88-3	-	Group 3	-	-
TALC 14807-96-6	-	Group 3	-	-

*IARC (International Agency for Research on Cancer)*

*Group 2A - Probably Carcinogenic to Humans*

*Not classifiable as a human carcinogen*

*OSHA (Occupational Safety and Health Administration of the US Department of Labor)*

*X - Present*

**Chronic toxicity** May cause adverse liver effects.  
**Target Organ Effects** Central nervous system, Central Vascular System (CVS), Eyes, kidney, Liver, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

<b>ATEmix (oral)</b>	7970 mg/kg
<b>ATEmix (dermal)</b>	5775 mg/kg
<b>ATEmix (inhalation-dust/mist)</b>	78.1 mg/l

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

65 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
ASPHALT, OXIDIZED 64742-93-4	56: 72 h Pseudokirchneriella subcapitata mg/L EC50	-	-
TOLUENE 108-88-3	433: 96 h Pseudokirchneriella subcapitata mg/L EC50 12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 12.6: 96 h Pimephales promelas mg/L LC50 static 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 54: 96 h Oryzias latipes mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static	5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static 11.5: 48 h Daphnia magna mg/L EC50
TALC 14807-96-6	-	100: 96 h Brachydanio rerio g/L LC50 semi-static	-

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

**Mobility**

No information available.

Chemical Name	Partition coefficient
PETROLEUM GASES, LIQUEFIED, SWEETENED 68476-86-8	<=2.8
TOLUENE 108-88-3	2.65

**Other adverse effects**

No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal of wastes** Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated packaging** Do not reuse container.

**US EPA Waste Number** D001

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
TOLUENE 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151	-	U220

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
TOLUENE 108-88-3	-	-	Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	-

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
TOLUENE 108-88-3	Toxic Ignitable

**14. TRANSPORT INFORMATION**

**DOT**

UN/ID no 1950  
 Proper shipping name: Aerosols, Limited Quantity (LQ)  
 Hazard Class 2.1  
 Emergency Response Guide Number 126

**IATA**

UN/ID no ID 8000  
 Proper shipping name: Consumer commodity  
 Hazard Class 9  
 ERG Code 9L

**IMDG**

UN/ID no 1950  
 Proper shipping name: Aerosols, Limited Quantity (LQ)  
 Hazard Class 2.1  
 EmS-No F-D, S-U

**15. REGULATORY INFORMATION**

**International Inventories**

TSCA Complies  
 DSL/NDSL Complies  
 EINECS/ELINCS Complies  
 ENCS Not Listed.  
 IECSC Complies  
 KECL Complies  
 PICCS Complies  
 AICS Complies

**Legend:**

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List



**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**US Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
TOLUENE - 108-88-3	1.0

**SARA 311/312 Hazard Categories**

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
TOLUENE 108-88-3	1000 lb	X	X	X

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
TOLUENE 108-88-3	1 lb	-	RQ 1 lb final RQ RQ 0.454 kg final RQ

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
TOLUENE - 108-88-3	Developmental Female Reproductive

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ASPHALT, OXIDIZED 64742-93-4	X	-	-
TOLUENE 108-88-3	X	X	X
STODDARD SOLVENT 8052-41-3	X	X	X
TALC 14807-96-6	X	X	X

**U.S. EPA Label Information**

**EPA Pesticide Registration Number** Not applicable

<b><u>NFPA</u></b>	Health hazards 2	Flammability 4	Instability 0	-
<b><u>HMIS</u></b>	Health hazards 2	Flammability 4	Physical hazards 0	Personal protection B

NFPA (National Fire Protection Association)  
HMIS (Hazardous Material Information System)

**Revision Date** 17-Jun-2015

**Disclaimer**

**The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.**

**End of Safety Data Sheet**